

ELECTRONIC TRACTION



INDOTRAC D is an advanced technology solid state circuitry Static / Intermittent traction unit. Moulded Aluminium gear box and metal gears gives long life to the equipment. It has silence smooth and powerful motor to pull the appropriate weight. The treatment time, Rest time & Hold time is controlled by micro controller. Separate tension control for cervical and pelvic.

FEATURES

- Micro controller based
- Large LCD display
- Soft touch keys
- Imported sturdy & noise less motor
- Moulded aluminium gear box
- Patient safety remote
- Easy to operate

TECHNICAL DATA

- Mains Voltage - 220 V/ 50 Hz
- Safety Class - Class I, Type BF (IEC 60601 -1)
- Dimensions - L x B x H – 28 x 31 x 28 cms
- Weight - 11 Kgs

SPECIFICATIONS

- Treatment Types - Continuous and Intermittent
- Traction force - 3 - 60 Kgs (120Kgs with Doubler)
- Hold Time - 10 - 80 sec (5sec step)
- Rest time - 1 - 20 sec (1sec step)
- Timer - 0 – 99 min. At the end of treatment time Acoustic signal and automatic reduction Of traction force

HMS Medical Systems

#9, 1st Cross Street, New Colony, Porur, Chennai - 600116.
Ph : +91 44 2476 0756, 2476 6576 Telefax : +91 44 2476 3773
Web : www.hms.co.in email : sales@hms.co.in